FIREAVERT

ELECTRIC STOVE
AUTO SHUTOFF
Model: FA-ES-HW

Specification Sheet

Be Protected In Minutes

Worldwide, structure fires from unattended cooking costs billions of dollars in damages every year. FireAvert's Auto Shutoff addresses and prevents this problem by turning off the stove before the fire ever ignites. Connect the stove to the Auto Shutoff and test it with the nearest smoke alarm. In the event the smoke alarm sounds due to improper use of the stove/cooktop, Auto Shutoff will cut power, eliminating the heat source to prevent a kitchen fire!



Features

- The only device on the market that responds to smoke, the earliest stage of a fire
- Suitable for all types of electrical stoves and cooktops
- Turns off the stove when smoke alarms sound
- Works with any Australian/New Zealand approved smoke alarm
- No batteries and maintenance free
- Electrical Current Detection causes activation only when stove is on and smoke alarm sounds
- Light indicates number of times activated
- Reusable; auto-reset occurs after 5 minutes if smoke alarms have stopped sounding and stove knobs are off
- Manually resets at the electrical switchboard or isolation switch

Installation Process

The Electric Stove Auto-Shutoff is easy to install with the help of your local electrician. Installation takes less than 15 minutes and protects you and your family from cooking fires. The Auto Shutoff is activated by the smoke alarm, cutting power to the stove/range and oven when the smoke alarm is sounding. To reset the stove after it cuts off power, simply turn the isolation switch or circuit breaker off and then back on again.

FIREAVERT

ELECTRIC STOVE
AUTO SHUTOFF
Model: FA-ES-HW

Specification Sheet

Specifications

Electrical Specifications

Operating Voltage	230/400 VAC
Amperage	40A 50-60Hz
Plug Configuration	Hardwire
Pole	1, 2, or 3 Pole Compatible
Wire	1.5mm² - 10mm² Accepted
Fire Rating	Housing PC/ABS fire retardant - UL94 (5VB,V-0)
Radio Frequency	Not Applicable

Physical Specifications

Dimensions	23.6 cm x 10.8 cm x 8 cm – (LxWxH)
Weight	0.7 kG
Color	Black
Operating Temperature Range	0°C to 37.8°C
Operating Humidity Range	0 to 80% RH non-condensing
Mounting	Optional
Stove/Ranges	Electric, up to 400V
Environmental	PB Free

LED Modes

LED Mode	White LED	Green LED	Red LED	Yellow LED
Power Up	Flash	Off	Flash (Cut Count)	Off
Standby	Off	Solid	Off	Off
Protection Mode	Off	Off	Solid	On During Auto-Reset

Approvals

Approved to AS/NZS 3100

Warranty

Click here to download the FireAvert Warranty

Contact

Web: fireavertaustralia.com.au
Email: enquiries@fireavertaustralia.com.au
Phone: +61 (0)419103429